AUTHOR INDEX TO VOLUME 8

Agrawal, A. K., 375
Alain, R., 335
Ari, N., 241

Barnes, P. R., 159, 213
Baum, C. E., 15, 375
Bernard, J., 335
Blumer, W., 241

Canavero, F. G., 125, 293
Cristina, S., 277

Damaskos, N. J., 71
D'Amore, M., 277
Daniele, V., 125, 293
Degauque, P., 311
Demoulin, B., 311

Engheta, N., 29

Feliziani, M., 277
Fimerelis, C., 1

Graglia, R. D., 125, 293

Harper, E., 37
Harrison, M. G., 37

Ianoz, M., 171

Kim, Y. U., 51
Koné, L., 311

Lee, K. S. H., 107

Martine, S., 335
Massoudi, H., 71

Nucci, C. A., 171

Smith, P. D., 85
Stevens, R. A., 159
Stone, A. P., 15

Taylor, C. D., 37
Tesche, F. M., 171, 213

Uslenghi, P. L. E., 71
Uzunoglu, N. K., 1

Vance, E. F., 365

Younan, N., 37

Zeddam, A., 311
Zuffada, C., 29

SUBJECT INDEX TO VOLUME 8

Behavior of wire structures subjected to electromagnetic pulse, rigorous analysis of, 335
Bounding of signal levels at terminations of multiconductor transmission-line network, 375

Current inducted in buried conductors, 365
Current waveforms, induced by broadside electromagnetic field on long wire, 85

Design of two-wire EMP simulator, field uniformity criteria, 29

Early-time response of infinitely long wire above finitely conducting plane earth to transient plane wave, 159
Electromagnetic pulse interaction with multi-conductor transmission lines, 293
EMP coupling to power lines, 277

High altitude electromagnetic pulse environment, resulting overhead line responses, 213

Peak directivity optimization in antenna arrays, under side lobe level constraints, 51

Scattering by circular cylindrical structure, composite and anisotropic: exact solution, 71

Terminated uniform two-wire transmission line, excited by plane electromagnetic field, response of, 241
Transequatorial VHF propagation, waveguide model for evening type: comparison with experiment for Euro-African sector, 1
Transient measurement record, extending, 37
Transmission line theory, field-to-transmission line coupling calculations, 171
Transmission lines:
  electromagnetic coupling to, 107
  spectral theory in presence of external electromagnetic sources, 125
Two-dimensional EM lenses, design via differential geometric scaling, 15

Voltages induced by disturbing wave, on coaxial cables or multi-wire shielded lines, 311